

INSTRUCTIONS FOR COMBINATION LOCK

OPENING THE SAFE—Use the OPENING Index



Opening the factory-set combination (50-50-50)

Turn the dial to the LEFT (counterclockwise) four complete turns stopping with 50 lined up on the OPENING Index on the fourth turn, Turn RIGHT until the dial stops . The combination lock bolt will retract and the safe may be opened.

NOTE: If you dial past the number where you were supposed to stop . you cannot reverse the dial to correct . The opening procedure must be repeated from the beginning.

To open the safe with previously-set three number combination(10-20-30) use the following procedures:

- 1) Using the OPENING Index , turn the dial to the LEFT and pass the first number of the combination , 10 , three times and stop exactly on 10 the fourth time.
- 2) Turn the dial to the RIGHT(clockwise) and pass 20 two times and stop exactly on 20 the third time .
- 3) Turn the dial to the LEFT(counterclockwise) and pass 30 once and stop exactly on 30 the second time
- 4) Turn the dial to the RIGHT(clockwise) , when the lock is open , the dial will stop .
- 5) To lock the combination lock , turn the dial four complete rotation to the LEFT(counterclockwise.)



CHANGING THE COMBINATION

To change the combination, you will need the existing combination and a Change Key . Procedures as Follow :

1. With lock bolt fully retracted (lock open) , before changing combinations , verify that the dial stops between 90 and 100 on the OPENING INDEX.
2. Dial the existing combination(10-20-30) , as previously described , on the CHANGING index , but stop the third dial combination (30) on exactly CHANGING INDEX not opening index .
3. On the back of the door , insert the Change key into the key hole . If the Change Key does not go it easily , the wheels are not aligned for changing . Redial the existing combination on the CHANGING INDEX.
4. Turn the Changing Key to the LEFT (Rotate90°CCW) until it stops . Leave the key in the lock .
5. Select a new combination , such as 40-50-60 . Never select number from 0 to 20 as the last number of the combination, this is a forbidden zone .
6. Still using the CHANGING INDEX , turn the dial to the LEFT and pass 40 three times and stop exactly on 40 the fourth time , aligning the number with the CHANGE Index
7. Turn the dial to the RIGHT and pass 50 two time and stop exactly on 50 the third time , aligning the number with the CHANGING Index.
8. Turn the dial to the Left pass 60 once and stop exactly on 60 the second time , aligning the number with the CHANGING Index. Leave the dial on 60 .
9. Turn the Changing Key to the RIGHT until it stops and remove the key.
10. Completely dial the new combination (40-50-60) using the OPENING INDEX several times to make sure the combination lock will open before you shut and lock the door of the safe .